

TOUCHSCREENS**INFORMATION**

17" Open Frame touchscreen monitor with edge-to-edge glass and Touch Through-Glass function for flexible integration



The ProLite TF1734MC-B8X is a 17" Open Frame touchscreen monitor designed for integration into kiosks, retail systems, interactive displays and custom installations. Its 10-point PCAP touch technology provides accurate multi-touch operation, while the edge-to-edge glass surface offers durability, scratch resistance and a clean, professional appearance.

With IP65-rated front protection, the screen is resistant to dust and splashing water from the front, making it suitable for demanding public and commercial environments. The anti-fingerprint coating helps keep the display clear and easy to use, even with frequent interaction.

For applications requiring additional protection, the Touch Through-Glass function allows reliable touch operation through a glass overlay up to 6 mm. The monitor can be installed in landscape, portrait or face-up orientation, while optional Open Frame mounting brackets support easy and secure integration into different installation designs.

For ease of integration, the monitor can be equipped with optional external mounting brackets ([OMK1-1](#)).



Touch works. Glass protects.

The display remains fully touch-responsive even when installed behind a protective glass layer. Ideal for kiosks, parcel lockers, self-service terminals and other public-facing installations where durability matters.



Reliable where conditions get tough

IP65 protection helps the monitor withstand dusty conditions and splashing water from any direction, making it suitable for more demanding environments.



Versatile by design

From wall-mounted interfaces to counter-based interaction, the monitor supports landscape, portrait and face-up installation, giving integrators more freedom to create intuitive touch solutions.



Open frame brackets

For ease of integration, the monitor can be equipped with optional external mounting brackets.

SPECIFICATION

01 DISPLAY CHARACTERISTICS

Diagonal	17", 43cm
Panel	TN
Native resolution	1280 x 1024 @75Hz (1.3 megapixel)
Aspect ratio	5:4
Panel brightness	350 cd/m ²
Brightness	300 cd/m ² with touch
Light transmittance	85%
Static contrast	1000:1 with touch
Response time (BTB)	5ms
Viewing zone	horizontal/vertical: 170°/160°, right/left: 85°/85°, up/down: 80°/80°
Horizontal Sync	31 - 80kHz
Viewable area W x H	338 x 270mm, 13.3 x 10.6"
Pixel pitch	0.264mm

02 TOUCH

Touch technology	projective capacitive
Touch interface	USB
Palm rejection	yes

03 FEATURES

Extra	anti-fingerprint coating, touch through-glass
Glass thickness	3mm
60950 Ball drop test	yes
Water and dust protection	IP65 (front)
OSD key lock	yes

04 GENERAL

OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, NL, PL
Control buttons	Menu, Scroll up/ Brightness, Scroll down/ Contrast, Select, Power
User controls	picture (contrast, brightness, H.position, V.position, phase, clock, auto adjust), advanced (color temp., sharpness), OSD (time out, position, H-position, V-position, Touch switch), option (reset, language, source select, display mode, factory)
Plug&Play	DDC2B

05 MECHANICAL

Orientation	landscape, portrait, face-up
--------------------	------------------------------

VESA mounting	100 x 100mm
----------------------	-------------

06 ACCESSORIES INCLUDED

Cables	power (1.8m), USB (1.8m), HDMI (1.8m), DP (1.8m)
Guides	quick start guide, safety guide
Other	AC adapter
Cable cover	yes

07 POWER MANAGEMENT

Power supply unit	external
Power supply	DC 12 V
Power usage	13W typical, 1.5W stand by, 0.3W off mode

08 SUSTAINABILITY

Regulations	RoHS support, ErP, WEEE, REACH
Energy efficiency class (Regulation class (EU) 2017/1369)	E
REACH SVHC	above 0.1%: Lead, Lead monoxide, Boric acid

09 DIMENSIONS / WEIGHT

Product dimensions W x H x D	369 x 307 x 47.5mm
Box dimensions W x H x D	387 x 145 x 455mm
Weight (without box)	3.6kg
Weight (with box)	5.2kg
EAN code	4948570127818



OPTIONAL BRACKETS,
PART DMK 1-1



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED