



# Shenzhen Absen Optoelectronic Co., Ltd.

## ABSENICON3.0 C110- Specifications

Version : V20210924

Parameter		Value			
Physical Parameter	Product Model	ABSENICON3.0 C110			
	Display Diagonal Size (Inch)	110			
	LED Type	1010			
	Display Size ( W×H ) / ( mm )	2450×1487×28.5			
	Pixel Per Display ( Pixels )	1920*1080			
	Display Weight ( kg ) ( Including frame and rim )	wall mounting	Hanging	wall to floor	mobile stand
	103			125	
Optoelectronic Parameter	Standard Brightness ( nit )	350			
	Refresh Rate ( Hz )	3,840			
	Contrast Ratio	4000:1			
	Color Temperature ( K )	6500			
	Viewing Angle(H/V) ( ° )	160/140			
	AC Operating Voltage ( V )	100 ~ 240			
	Power Consumption ( Max./Avg. ) ( W )	1200/400			
Application Parameter	Applying Space	40			
	Storage Temperature ( °C )	-40 ~ +60			
	Operating Temperature ( °C )	-10 ~ +40			
	Storage Humidity ( RH )	10% ~ 85%			
	Operating Humidity ( RH )	10% ~ 80%			
	IP Rating ( Front/Rear )	IP40/IP21			
	Maintenance	Front			
	Certificate	CCC,CE,FCC			

Remark:Power consumption tolerance: ±15%, according to the actual situation.



# Shenzhen Absen Optoelectronic Co., Ltd.

## ABSENICON3.0 C138- Specifications

Version : V20210819

Parameter		Value			
Physical Parameter	Product Model	ABSENICON3.0 C138			
	Display Diagonal Size (Inch)	138			
	LED Type	1212			
	Display Size ( W×H ) / ( mm )	3060*1830*28.5			
	Pixel Per Display ( Pixels )	1920*1080			
	Display Weight ( kg ) ( Including frame and rim )	wall mounting	Hanging	wall to floor	mobile stand
	160			180	
Optoelectronic Parameter	Standard Brightness ( nit )	350			
	Refresh Rate ( Hz )	3,840			
	Contrast Ratio	5000:1			
	Color Temperature ( K )	6500			
	Viewing Angle(H/V) ( ° )	160/140			
	AC Operating Voltage ( V )	100 ~ 240			
	Power Consumption ( Max./Avg. ) ( W )	1500/500			
Application Parameter	Applying Space	60			
	Storage Temperature ( °C )	-40 ~ +60			
	Operating Temperature ( °C )	-10 ~ +40			
	Storage Humidity ( RH )	10% ~ 85%			
	Operating Humidity ( RH )	10% ~ 80%			
	IP Rating ( Front/Rear )	IP40/IP21			
	Maintenance	Front			
	Certificate	CCC,CE,FCC			

Remark:Power consumption tolerance: ±15%, according to the actual situation.



# Shenzhen Absen Optoelectronic Co., Ltd.

## ABSENICON3.0 C165 - Specifications

Version : V20210819

Parameter		Value			
<b>Physical Parameter</b>	Product Model	ABSENICON3.0 C165			
	Display Diagonal Size (Inch)	165			
	LED Type	1515			
	Display Size ( W×H ) / ( mm )	3670*2173*28.5			
	Pixel Per Display ( Pixels )	1920*1080			
	Display Weight ( kg ) ( Including frame and rim )	wall mounting	Hanging	wall to floor	mobile stand
	218				
<b>Optoelectronic Parameter</b>	Standard Brightness ( nit )	350			
	Refresh Rate ( Hz )	3,840			
	Contrast Ratio	4000:1			
	Color Temperature ( K )	6500			
	Viewing Angle(H/V) ( ° )	160/140			
	AC Operating Voltage ( V )	200 ~ 240			
	Power Consumption ( Max./Avg. ) ( W )	1800/600			
<b>Application Parameter</b>	Applying Space	100			
	Storage Temperature ( °C )	-40 ~ +60			
	Operating Temperature ( °C )	-10 ~ +40			
	Storage Humidity ( RH )	10% ~ 85%			
	Operating Humidity ( RH )	10% ~ 80%			
	IP Rating ( Front/Rear )	IP40/IP21			
	Maintenance	Front			
	Certificate	CCC,CE,FCC			

*Remark: Power consumption tolerance: ±15%, according to the actual situation.*